

單迴路溫度控制器 3200系列 選型表

1	2	3	4	5	6	7	8	9	10	11	12	13	14
---	---	---	---	---	---	---	---	---	----	----	----	----	----

1. Model No.	
1/16 DIN size	3216
1/8 DIN size vertical	3208
1/8 DIN horizontal	32h8
1/4 DIN size	3204

2. Function	
Controller	CC
Programmer	CP
valve controller	VC
Valve programmer	VP

3. Power Supply	
24Vac/dc	VL
100-230Vac	VH

4. Output 1 & 2 3216				
OP1	OP2			
L	X	X	X	
L	R	X	X	
R	R	X	X	
L	L	X	X	
L	D	X	X	
D	D	X	X	
D	R	X	X	
R	C	X	X	
L	C	X	X	
D	C	X	X	
Not available with low voltage supply option.				
L	T	X	X	
T	T	X	X	
L = Logic R = Relay T = Triac D = 0-20mA non-isolated C = 0-20mA isolated				

4. Outputs 1, 2 and 3 3208/H8/04				
OP1	OP2	OP3		
L	R	R	X	
R	R	R	X	
L	L	R	X	
L	R	D	X	
R	R	D	X	
D	D	D	X	
L	L	D	X	
L	D	D	X	
D	R	D	X	
Not available with low voltage supply option.				
L	T	R	X	
T	T	R	X	
L	T	D	X	
T	D	D	X	
T	T	D	X	
L = Logic R = Relay T = Triac D = 0-20mA non-isolated outputs 1 and 2 D = 0-20mA isolated output 3				

5. AA Relay (OP4)	
Disabled	X
Relay (Form C)	R

6. Options	
Not fitted	XXX
EIA485 & Digital input A	4XL*
EIA232 & Digital input A	2XL*
EIA485, CT & Dig in A	4CL
EIA232, CT & Dig in A	2CL
Digital input A	XXL*
CT & Digital input A	XCL
Remote SP and Logic IP	RCL
4-wire EIA485 (EIA422) Comms (3216 only)	6XX
* 3216 only	

7. Fascia colour/type	
Green	G
Silver	S
Wash down fascia (not 32h8/04)	W

8/9 Product/Manual Language	
English	ENG
French	FRA
German	GER
Italian	ITA
Spanish	SPA

10. Extended Warranty	
Standard	XXXXX
Extended	WL005

11. Certificates	
XXXXX	None
Cert of conformity	CERT1
Factory calibration	CERT2

12. Custom Label	
None	XXXXX

13. Specials Number	
None	XXXXXX
250Ω ; 0-5Vdc OP	RES250
500Ω ; 0-10Vdc OP	RES500